Machine Learning - Option Pricing, Calibration, Hedging -- Deep Hedging -

WBS Quant Conference - Workshop, Rome 2019

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

UCT, BUW, Finciraptor finciraptor.de, joerg.kienitz@gmx.de



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 1/56

イロト 不良 トイヨト イヨト

This presentation and any accompanying material are being provided solely for information and general illustrative purposes. The author will not be responsible for the consequences of reliance upon any information contained in or derived from the presentation or for any omission of information therefrom and hereby excludes all liability for loss or damage (including, without limitation, direct, indirect, foreseeable, or consequential loss or damage and including loss or profit and even if advised of the possibility of such damages or if such damages were foreseeable) that may be incurred or suffered by any person in connection with the presentation, including (without limitation) for the consequences of reliance upon any results derived therefrom or any error or omission whether negligent or not. No representation or warranty is made or given by the author that the presentation or any content thereof will be error free, updated, complete or that inaccuracies, errors or defects will be corrected.

The views are solely that of the author and not of his employer, Quaternion Risk Management GmbH. The Chatham House rules apply.

The presentation may not be reproduced in whole or part or delivered to any other person without prior permission of the author.

(日)



Introduction

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

・ ロ ト ・ 同 ト ・ 三 ト ・ 三 ト

Outline

Introduction

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem
- 2 Recurrent Neural Networks (RNN)
 - Predicting Sequences
 - Long-Term-Short-Term Networks (LSTM)
- 3 Deep Hedging
 - Black/Scholes Numerical Results
 - Heston Results

A D N A B N A B N A B N

Hedging as Sell Side Business Model

- Issue a derivative X and sell to clients
- Replicate payoff of derivative X by a portfolio with a trading strategy ϕ that only trades in the underlying S
- Being long the portfolio and short the derivative is (theoretically) riskless ⇒ make profits in fees

Deep Learning

- Machine Learning using neural networks is called *Deep Learning*, if it has a "high" number of hidden layers in order to capture non-linearities (depending on the context "high" means just "> 2")
- "Deep Hedging" is the idea to use deep learning to find the hedging strategy ϕ

Deep Hedging is an active field of research. This presentation is based mostly on the following sources:

• Black/Scholes model: M. Groncki's blog post & notebook (many thanks for allowing us to use it for this talk)

https://ipythonquant.wordpress.com/2018/06/05/

option-hedging-with-long-short-term-memory-recurrent-neural-networks-part-i/

• Heston model: Bühler, Gonon, Teichmann, Wood. *Deep Hedging*

https://arxiv.org/abs/1802.03042

• ETH Lectures (Teichmann)

https://people.math.ethz.ch/~jteichma/index.php?content=teach_mlf2019

• LSTM Intro (N. Nowaczyk)

https://github.com/niknow/machine-learning-examples

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 6/56

Outline



Introduction

• Recap of Math Finance Setup & Notation

- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

イロト イポト イヨト イヨト

Definition (standard market)

Let $(\Omega, \mathcal{F}, \mathbb{P})$ be a probability space and let

 $dS_t = \mu_t(S_t)dt + \sigma_t(S_t)dW_t$

be an Ito process of *tradable assets* S^1, \ldots, S^p , such that $\mu \in L^1$, $\sigma \in L^2$ (pathwise). Here, W_t is a multi-variate Brownian motion. Let $\mathbb{F} := (\mathcal{F}_t)_{t \ge 0}$ be the augmented natural filtration generated by W_t . We assume that $N := S^1$ is the chosen numeraire and that all deals mature at a maximum maturity T > 0.

イロト イポト イヨト イヨト

Definition (trading strategy)

In a standard market with assets S^1, \ldots, S^p , a *trading strategy* is a predictable adapted process $\phi : \Omega \times [0, T] \to \mathbb{R}^p$. The process

$$\Pi(t) := \phi(t)S(t) := \sum_{i=1}^p \phi_i(t)S_i(t),$$

is the associated portfolio value process. A strategy ϕ is called self-financing if

$$d\Pi(t) = \phi(t) dS(t).$$

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 9/56

(日)

Definition (arbitrage opportunity)

A trading strategy ϕ is an *arbitrage opportunity*, if its portfolio value process Π satisfies

 $\Pi(0)=0, \quad \exists 0\leq t\leq \mathcal{T}:\Pi(t)\geq 0 \text{ a.s. and } \mathbb{P}[\Pi(t)>0]>0.$

A market is *arbitrage free*, if there exists no arbitrage opportunities.

Theorem

If there exists an equivalent martingale measure \mathbb{Q} , then the market is arbitrage free.

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 10/56

(日)

Definition

A contigent claim / derivative is an \mathcal{F}_T -measurable random variable V_T . A trading strategy ϕ replicates V_T if its associated value process Π satisfies $\Pi_T = V_T$. A market is complete if every claim can be replicated.

Theorem

If there exists a unique equivalent martingale measure \mathbb{Q} , then the market is arbitrage free and complete.

The strategy ϕ can be used to hedge the derivative as $\Pi_t = \sum_{i=1}^{p} \phi_t^i S_t^i = V_t.$

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

イロト 不得 トイヨト イヨト

Definition

The 2-asset market comprising of a deterministic bank account and a GBM for a single stock,

$$dB_t = rB_t dt,$$
 $dS_t = \mu S_t dt + \sigma S_t dW_t$

is called *Black/Scholes model*.

Theorem

The Black/Scholes model is arbitrage-free and complete. It has the explicit representation

$$B_t = B_0 e^{rt}, \qquad \qquad S_t = S_0 e^{(\mu - \frac{\sigma^2}{2})t + \sigma W_t}$$

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

(日)

Theorem

The price of a European call option $C_T = (S_T - K)^+$ with strike K in the Black/Scholes model is given by

$$C_{t} = \Phi(d_{1})S_{t} - \Phi(d_{2})e^{-r(T-t)}K$$

$$d_{1} = (\ln(\frac{S_{t}}{K}) + (r + \frac{\sigma^{2}}{2})(T-t))/(\sigma\sqrt{T-t})$$

$$d_{2} = d_{1} - \sigma\sqrt{T-t},$$

where Φ is the standard normal cdf. Furthermore,

$$\Delta_t = \frac{\partial C_t}{\partial S_t} = \Phi(d_1).$$

is the amount of stock necessary to replicate C_t .

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

< □ > < □ > < □ > < □ > < □ > < □ >

Definition

The Heston model for a stock price is defined by

$$\begin{split} dS_t^1 &= \sqrt{V_t} S_t dB_t, \qquad S_0^1 = s_0, \\ dV_t &= \alpha (b - V_t) dt + \sigma \sqrt{V_t} dW_t \qquad , V_0 = v_0, \end{split}$$

where $\alpha, b, \sigma, s_0, v_0 > 0$ and B_t , W_t are Brownian motions correlated with $\rho \in [-1, 1]$.

The stochastic volatility V_t cannot be traded directly. Thus, we introduce an idealized variance swap on it with price process

$$S_t^2 := \mathbb{E}_{\mathbb{Q}}\Big[\int_0^T V_s ds \mid \mathcal{F}_t^H\Big], \quad \mathcal{F}_t^H = \sigma((S_s^1, V_s), 0 \le s \le t)$$

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

イロト イヨト イヨト イヨト

The variance swap can be written as

$$S_t^2 = \int_0^t V_s ds + L(t, V_t), \quad L(t, v) = \frac{v - b}{\alpha} (1 - e^{-\alpha(T-t)} + b(T-t)).$$

Let $g : \mathbb{R} \to \mathbb{R}$ be the European payoff of an option. By the Markov property, its price process can be written as $C_t = \mathbb{E}_{\mathbb{O}}[g(S_t^1) \mid \mathcal{F}_t^H] = u(t, S_t^1, V_t)$. We obtain

$$g(S_T^1) = q + \int_0^T \phi_t^1 dS_t^1 + \int_0^T \phi_t^2 dS_t^2.$$

where $q = \mathbb{E}_{\mathbb{Q}}[g(S_T^1)], \phi_t^1 = \partial_s u(t, S_t^1, V_t), \phi_t^2 = \frac{\partial_v u(t, S_t^1, V_t)}{\partial_v l(t, V_t)}.$

Machine Learning- Option Pricing, Calibration, Hedging - 15/56

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Outline

1 Inti

Introduction

• Recap of Math Finance Setup & Notation

• Hedging: Theory vs. Practice

- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

イロト イポト イヨト イヨト

Practical Problem 1: Trading is not continuous

In theory, continuous trading is and a bank can short the option C_t and hedge it by going long the replication portfolio Π with the trading strategy ϕ (for both Black/Scholes and Heston). This is called *Delta Hedging* and would result in a net position of:

$$-C_t+\Pi_t=0.$$

In reality, continuous trading is not possible and we have to work on a discretized grid $0 = t_0 < \ldots < t_n = T$ leaving us with a *hedge error* at maturity of

$$-C_{T}+p_{0}+\underbrace{\sum_{k=0}^{n-1}\phi_{t_{k}}(S_{k+1}-S_{k})}_{=:(S\cdot\phi)_{T}},$$

where p_0 is an initial injection of cash into the trading strategy ϕ .

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 17/56

・ロト ・ 母 ト ・ ヨ ト ・ ヨ ト

In theory, we have assumed that the market is complete and thus every derivative can be perfectly hedged and that all trading is frictionless.

In reality, a market might not be complete and all trading comes with friction such as transaction costs c_k . Thus, this leaves us with a total portfolio value of

$$PL_{T}(Z, p_{0}, \phi) := -C_{T} + p_{0} + (S \cdot \phi)_{T} - \underbrace{\sum_{k=0}^{n} c_{k}(\phi_{t_{k}} - \phi_{t_{k-1}})}_{=:C_{T}(\phi)},$$

and we can no longer assume that this will balance out to zero, but we can minimize this random variable in some metric!

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

(日)

Outline

Introduction

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice

Risk Measures

- General Hedging Problem
- 2 Recurrent Neural Networks (RNN)
 - Predicting Sequences
 - Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

イロト イポト イヨト イヨト

Definition

Let $(\Omega, \mathcal{F}, \mathbb{P})$ be a probability space and let \mathcal{X} be the space of all real valued random variables on Ω . Then $\rho : \mathcal{X} \to \mathbb{R}$ is a *convex risk measure*, if for any X, X_1, X_2 (representing portfolio assets):

- Monotone decreasing: $X_1 \ge X_2 \Longrightarrow \rho(X_1) \le \rho(X_2)$.
- Onvex:

 $\forall \alpha \in [0,1] : \rho(\alpha X_1 + (1-\alpha)X_2) \le \alpha \rho(X_1) + (1-\alpha)\rho(X_2).$

3 Cash-Invariant: $\forall c \in \mathbb{R} : \rho(X + c) = \rho(X) - c$.

The measure ρ is called *normalized* if $\rho(0) = 0$.

イロト 不得 トイヨト イヨト

3

Theorem

Let ρ be a convex risk measure and \mathcal{H} be the space of all constrained trading strategies. If $C_T(\cdot)$ and \mathcal{H} are convex, then

$$X\mapsto \pi(X):=\inf_{\phi\in\mathcal{H}}
ho(X+(\phi\cdot S)_{\mathcal{T}}-\mathcal{C}_{\mathcal{T}}(\phi))$$

is a convex risk measure as well.

イロト イポト イヨト イヨト

Definition

Let $(\Omega, \mathcal{F}, \mathbb{P})$ be a probability space. For any $\alpha \in [0, 1[$, the risk measure

$$X\mapsto
ho(X):={\sf ES}(X):=rac{1}{1-lpha}\int_0^{1-lpha}{\sf VaR}_\gamma(X)d\gamma$$

is called expected shortfall with risk-aversion level α . Here,

$$\operatorname{VaR}_{\gamma}(X) := \inf\{m \in \mathsf{R} : \mathbb{P}(X < -m) \leq \gamma\}$$

is the Value-at-risk with confidence level γ .

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 22/56

(日)

Outline

Introduction

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

イロト イポト イヨト イヨト

Let $S = (S_1, \ldots, S_p)$ be tradable assets in a market and X be the payout of a derivative. We assume that $0 = t_0 < \ldots < t_n = T$ are the distinct points at which trading is possible. We want to find a trading strategy $\phi = (\phi_0, \ldots, \phi_n)$, $\phi_j \in \mathbb{R}^k$, such that ϕ attains

$$\pi(X) = \inf_{\phi \in \mathcal{H}} \rho(X + (\phi \cdot S)_{\mathcal{T}} - C_{\mathcal{T}}(\phi))$$

for some convex risk measure ρ .

Idea: Generate realizations of *S* and "learn" the trading strategy ϕ at each point in time t_k .

Problem: ϕ_t depends on t!

1 Introductio

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

A D N A B N A B N A B N



• Recap of Math Finance Setup & Notation

- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

A D N A B N A B N A B N

Usually, an artificial neural network (ANN) needs an input X to predict an output y. How to use ANNs if the input is a sequence X_t and the output is a sequence y_t ?

- Use a big NN with either fixed length vector input/outputs X_{t1},..., X_{tn} and y_{t1},..., y_{tn} or input/output pairs (X, t), (y, t).
- **2** Use a separate NN for each point t_k .
- Use a RNN!

イロト 不得 トイラト イラト 一日

Idea 1: Train one huge network



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 28/56

A D N A B N A B N A B N

Idea 1: Pros and Cons

Pros

- easy to understand
- straight-forward to implement

Cons

- resulting NN might need to be huge
- training set required to train the network might be huge
- resulting computational power required might be huge

(日)

Idea 2: Train one Network for each element



Machine Learning- Option Pricing, Calibration, Hedging - 30/56

イロト イポト イヨト イヨト

Pros

- resulting NN can be much smaller
- still easy to understand and straight-forward to implement

Cons

- the NN in later positions of the sequences might struggle to make accurate predictions
- predictions are made by independent NN, thus the output might suffer from consistency issues

イロト 不得 トイヨト イヨト

Origin of this approach: NLP

- Assume we have a text and the quantity to predict is the last word in the sentence. If the second sentence is: *Today is* <u>*Tuesday*</u>, this can be quite hard. But if the first sentence is: <u>*Yesterday was Monday*</u>, then this becomes a lot easier! Thus a chain of networks can be much more efficient if information is transported through time. (Short Term Memory)
- However, if the t = 12 sentence is Roses are <u>red</u>, then the information that the predicted word at t = 1 was Tuesday is not helpful and might actually be harmful. (Long Term Memory)
- Making the prediction at t depend on everything before, blows up the size of the networks. Thus, one needs an efficient way to manage short term and long term memory in these networks to make accurate predictions!

イロト 不得 トイヨト イヨト 二日

Introductio

- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem

2 Recurrent Neural Networks (RNN)

- Predicting Sequences
- Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

イロト イポト イヨト イヨト

Solution: Cell States



Machine Learning- Option Pricing, Calibration, Hedging - 34/56

イロト イポト イヨト イヨト

Definition (LSTM)

A Long-Term-Short-Term-Memory neural network is a tuple LSTM = LSTM(W, U, b, τ, σ) consisting of

- a number *m* of units and a number *k* of features,
- a 4-tuple W of matrices W_i, W_f, W_c, W_o ∈ ℝ^{k×m} called input, forget, cell and output kernels,
- a 4-tuple U of matrices $U_i, U_f, U_c, U_o \in \mathbb{R}^{m \times m}$ called *input*, *forget*, *cell* and *output recurrent kernels*,
- a 4-tuple b of vectors $b_i, b_f, b_c, b_o \in \mathbb{R}^m$ called *input*, *forget*, *cell* and *output bias*,
- two functions $\sigma, \tau : \mathbb{R} \to \mathbb{R}$ called *activation* and *recurrent activation*.

None of the parameters are time-dependent!

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

▲□▶ ▲□▶ ▲□▶ ▲□▶ □ ののの

LSTM Feedforward

Definition

Let LSTM = LSTM(W, U, b, τ, σ) and $T \in \mathbb{N}$. Any sequence $x = (x_1, \ldots, x_T)$, $x_t \in \mathbb{R}^k$, is called an *input sequence*. We recursively define:

nput:
$$i_t := \tau(x_t \odot W_i + h_{t-1} \odot U_i + b_i) \in \mathbb{R}^m$$
, (1)

$$\text{forget: } f_t := \tau(x_t \odot W_f + h_{t-1} \odot U_f + b_f) \in \mathbb{R}^m, \quad (2)$$

candidate:
$$\tilde{c}_t := \sigma(x_t \odot W_c + h_{t-1} \odot U_c + b_c) \in \mathbb{R}^m$$
, (3)

output:
$$o_t := \tau(x_t \odot W_o + h_{t-1} \odot U_o + b_o) \in \mathbb{R}^m$$
, (4)

cell:
$$c_t := f_t \bullet c_{t-1} + i_t \bullet \tilde{c}_t \in \mathbb{R}^m$$
, (5)

carry:
$$h_t := o_t \tau(c_t) \in \mathbb{R}^m$$
. (6)

Conventions: All vectors are row vectors, $c_0 := 0$, $h_0 := 0$, \odot denotes matrix-vector multiplication, \bullet denotes the element-wise multiplication of vectors, σ and τ are applied elementwise. Finally, the function $F_T : \mathbb{R}^{k \times T} \to \mathbb{R}^m$, $x = (x_1, \ldots, x_T) \mapsto h_T$ is called, the *feedforward of* LSTM *of length* T.

Jörg Kienitz / Nikolai Nowaczyk, Quaternion

LSTM Gate Representation



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 37/56

イロト イボト イヨト イヨト

2

- Recurrent Neural Networks in general and LSTMs in particular exist in many different variants.
- The internal structure of every node is a neural network and in principle, one can play around with any choice of architecture.
- Popular choices are hidden layers or different activation functions.
- The choices made above are in line with the keras implementation of LSTM.

(日)

Outline



- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem
- 2 Recurrent Neural Networks (RNN)
 - Predicting Sequences
 - Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

A D N A B N A B N A B N

Deep Hedging

- Deep Hedging is the technique of applying a recurrent neural network, for example the LSTM, to obtain a trading strategy φ of portfolio hedging a derivative security by using realizations of the underlying S as inputs.
- By giving the training algorithm of the neural network a risk metric such as ES as the cost function, the neural network will solve the problem of finding the optimal hedging strategy automatically. Thus, this is an instance of unsupervised learning.
- Generating the sample paths of the underlying is a non-trivial finance problem, which needs to be solved by Monte Carlo methods as usual.

イロト イヨト イヨト イヨト 二日

Outline



- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem
- 2 Recurrent Neural Networks (RNN)
 - Predicting Sequences
 - Long-Term-Short-Term Networks (LSTM)

O Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

A D N A B N A B N A B N

- The easiest example is provided by using an LSTM to learn the Δ-hedging strategy of a Call Option in the Black/Scholes model.
- There is a nice blog post and a Jupyter notebook by M. Groncki on this topic (thanks for allowing us to use it in this workshop!):

```
https://ipythonquant.wordpress.com/2018/06/05/
```

```
option-hedging-with-long-short-term-memory-recurrent-neural-networks-part-i/
```

https://github.com/mgroncki/DataScienceNotebooks/tree/master/DeepHedging

 In the following, we summarize a (slightly modified) version of Groncki's results.

(日)

- We consider the Black/Scholes model S_t with $\mu = 0$, $\sigma = 20\%$ on a daily grid with a T = 1M horizon.
- We train an LSTM on 500k realizations on all 30 days.
- We present the discretization error of the Black/Scholes strategy and perform various comparisons between the analytic Black/Scholes-Delta and the strategy obtained by the LSTM.

イロト イポト イヨト イヨト

1) Out of Sample Test (same moneyness): Deltas



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 44/56

イロト イボト イヨト イヨト

1) Out of Sample Test (same moneyness): Boxplot



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 45/56

イロト イポト イヨト イヨト

2) Out of Sample Test (different moneyness): Deltas



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging -46/56

イロト イボト イヨト イヨト

2) Out of Sample Test (different moneyness): Boxplot



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 47/56

イロト イポト イヨト イヨト

3) Out of Sample Test (different drift): Deltas



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 48/56

(日)

3) Out of Sample Test (different drift): Boxplot



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 49/56

イロト イポト イヨト イヨト

4) Out of Sample Test (different volatility): Deltas



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 50/56

イロト 不得 トイヨト イヨト

4) Out of Sample Test (different volatility): Boxplot



Jörg Kienitz / Nikolai Nowaczyk, Quaternion

Machine Learning- Option Pricing, Calibration, Hedging - 51/56

イロト イボト イヨト イヨト

Outline



- Recap of Math Finance Setup & Notation
- Hedging: Theory vs. Practice
- Risk Measures
- General Hedging Problem
- 2 Recurrent Neural Networks (RNN)
 - Predicting Sequences
 - Long-Term-Short-Term Networks (LSTM)

3 Deep Hedging

- Black/Scholes Numerical Results
- Heston Results

A D N A B N A B N A B N

• We now present the results obtained by Bühler et al. in:

https://arxiv.org/abs/1802.03042

• The setup is the discretized Heston model as discussed above and a Call Option as a derivative.

イロト イポト イヨト イヨト

Model Hedge vs Deep Hedge $\alpha = 50\%$



A D N A B N A B N A B N

Model Hedge vs Deep Hedge $\alpha = 50\%$ at fixed time slice

-0.04 -0.06 -0.08 -0.10

0.04 0.04





Jörg Kienitz / Nikolai Nowaczyk, Quaternion

100 102

Machine Learning- Option Pricing, Calibration, Hedging - 55/56

イロト 不得 トイラト イラト 一日

Further Research Questions

 The Black/Scholes pricing function has also been studied and can be learned (including the time-dependence) with just one NN:

https://arxiv.org/abs/1901.08943v2

Given that the Δ is Black/Scholes is "easier" than the pricing, is LSTM really necessary?

- Can Groncki's approach be improved such that one has one NN to price options for all (reasonable) choices of moneyness?
- How to systematically evaluate such an NN approach? What would be needed to pass model validation?
- Can one gain insights into the problem by studying the topology of a NN that is (approximately) optimal in a certain sense?

イロト 不得 トイヨト イヨト